

POLARIS®

OFF-ROAD VEHICLES

THE WORLD LEADER IN OFF-ROAD

STOP



POLARIS
GENERAL

POLARIS
RANGER

POLARIS
RZR

POLARIS
SPORTSMAN

POLARIS
ACE

POLARIS®

OFF-ROAD VEHICLES

> BEST SELLING IN EVERY CATEGORY

For 34 years, Polaris® has built the world's best off-road vehicles. Engineered with class-leading performance, and infused with unmatched capabilities and unrivaled toughness. Nothing else comes close.



POLARIS
RANGER

P3



POLARIS
GENERAL

P7



POLARIS
RZR

P9



POLARIS
SPORTSMAN

P13

DRIVEN TO DO MORE™



> BUILT FOR A JOB DONE RIGHT.

While others aspire, RANGER® continues to define the utility side-by-side category with barrier-breaking innovation, class-leading performance, an unstoppable work ethic and a never quit mentality.

RANGER XP® 1000 EPS



> CONNECT AND TAKE COMMAND

The RIDE COMMAND® factory-installed package is now available on select 3-seat RANGER XP® 1000 models, including the NorthStar® Edition. Equipped with a 7" glove-touch display, front and rear cameras, in-dash speakers, built-in GPS navigation and Bluetooth® connectivity.

RIDE COMMAND® PACKAGE AVAILABLE ON SELECT RANGER® MODELS



RANGER XP® 1000 NORTHSTAR® EDITION

> COMFORT AT YOUR CONTROL

The NorthStar® Edition is equipped with the premium RANGER® Pro Shield™ cab system with 3-times better dust control over the competition. It features factory-installed heating and conditioning to keep you working comfortably in any climate.

NORTHSTAR® EDITION AVAILABLE IN MULTIPLE COLORS

CHOOSE YOUR RANGER®

2-SEAT MODEL

BEST-IN-CLASS UTILITY VALUE

- » 2-SEAT CAPACITY
- » UP TO 44 HP
- » 1,500 LB TOWING CAPACITY
- » 10" GROUND CLEARANCE



MODEL SHOWN: RANGER® 570 EPS

3-SEAT MODEL

MAXIMUM CAPABILITY

- » 3-SEAT CAPACITY
- » UP TO 82 HP
- » UP TO 2,500 LB TOWING CAPACITY
- » UP TO 13" GROUND CLEARANCE



MODEL SHOWN: RANGER XP® 1000 EPS

CREW MODEL

COMFORTABLE SEATING UP TO 6

- » UP TO 82 HP
- » UP TO 2,500 LB TOWING CAPACITY
- » UP TO 1,750 LB PAYLOAD CAPACITY
- » UP TO 13" GROUND CLEARANCE



MODEL SHOWN: RANGER CREW® XP 1000 EPS

SEE FULL SPECS ON PAGE 19



*Excluding High Lifter Editions. See your authorized Polaris dealer for details.

THE NEW STANDARD

FOR 6 PASSENGER UTILITY



RANGER CREW XP 1000 EPS

> MORE RUGGED. MORE REFINED. MORE RANGER.™

82

HORSEPOWER

2,500 LB

TOWING CAPACITY

13 IN

GROUND CLEARANCE

> UNDISPUTED KING OF MUD



RANGER XP 1000 EPS HIGH LIFTER EDITION

> EXTREME MUD PERFORMANCE

- » NEW! REDESIGNED PREMIUM HALF DOORS WITH 1" WATER DRAINS
- » NEW! GEARED REVERSE TRANSMISSION
- » HIGH MOUNTED AIR INTAKES & VENT LINES
- » 82 HP WITH MUD SPECIFIC CAPABILITIES
- » 28" OUTLAW - 2 TIRES



> MUD WITH THE ENTIRE CREW

RANGER CREW XP 1000 EPS HIGH LIFTER EDITION

> BEST-IN-CLASS POWER



RANGER 570 EPS



RANGER XP 900 EPS

> WORLD'S BEST-SELLING UTILITY SXs

BUILT FOR LIFE



POLARIS® GENERAL® 1000 EPS RIDE COMMAND

ANY TASK. ANY TRAIL.

A day of chores or a day on trails, anything goes with Polaris® GENERAL®. Packed with the ideal combination of power, capability, control, and comfort, it's the ultimate do-it-all, accept-no-excuses performance rec-utility vehicle. Whether you're in search of big adventure, hauling big loads, or tracking big game, Polaris® GENERAL® is always ready.



POLARIS GENERAL® 1000 EPS DELUXE

UNSTOPPABLE POWER

100 HORSEPOWER | **600 LB** CARGO CAPACITY | **1,500 LB** TOWING CAPACITY



POLARIS® GENERAL® 4 1000 EPS

UNCOMPROMISING CAPABILITIES

12 IN GROUND CLEARANCE | **13.3 IN** SUSPENSION | **0-40 MPH** CLASS-LEADING ACCELERATION

CHOOSE YOUR GENERAL®

BASE

- » 1000 PROSTAR® 100 HP ENGINE
- » STANDARD HALF-DOORS
- » ELECTRONIC POWER STEERING (EPS)
- » DUMPING BOX & TAILGATE
- » LOCK & RIDE® COMPATIBLE
- » VERSATRAC TURF MODE



MODEL SHOWN: POLARIS® GENERAL® 1000 EPS

BASE FEATURES PLUS:

PREMIUM

BASE FEATURES PLUS:

- » AUTOMOTIVE PAINT
- » MATTE BLACK CAST ALUMINUM WHEELS
- » LOW-PROFILE FRONT BUMPER
- » POLARIS® HD 4,500 LB WINCH



MODEL SHOWN: POLARIS® GENERAL® 1000 EPS PREMIUM

DELUXE

PREMIUM FEATURES PLUS:

- » FOX® 2.0 PODIUM X QS3 SHOCKS
- » POLARIS® LOCK & RIDE® SPORT ROOF
- » MTX® PREMIUM SOUNDBAR
- » CONVEX REARVIEW MIRROR



MODEL SHOWN: POLARIS® GENERAL® 1000 EPS DELUXE

MULTI-PASSENGER

- » LOW-PROFILE FRONT BUMPER
- » POLARIS® HD 4,500 LB WINCH
- » NEW FOX® 2.0 PODIUM X QS3 SHOCKS
- » 27" GBC® DIRT COMMANDER 8-PLY TIRES



MODEL SHOWN: POLARIS® GENERAL® 4 1000 EPS

SEE FULL SPECS ON PAGE 25

LIVE WIDE OPEN™



> THE DRIVING FORCE IN OFF-ROAD

Through extensive engineering, RZR® achieves the pinnacle of extreme performance with an optimally balanced chassis and a formidable combination of power, suspension and agility. Giving you the confidence to push beyond your limits.

> THE BEAST BIGGER AND BADDER

168 HORSEPOWER | **72IN** WHEELBASE | **25IN** USABLE TRAVEL



> NASTY OUTSIDE

Cut more aggressively with menacing looks & wicked LED accents, all hint at the heart of the animal within.



> NICE INSIDE

A new driving position with race-inspired ergonomics, and a redesigned interior with premium digital displays for navigating rugged terrain at speed.

ALL-NEW

POLARIS
**RZR XP4
TURBO S**

72" Width. 168 HP. 32" Tires. 25" Travel. When the terrain is unrelenting and landscape unknown, there's no room for pretenders.





ALL-NEW

POLARIS RZR XP TURBO S

FEAR THE BEAST

The most intimidating and dominating sport side-by-side ever unleashed and you're in control. Engineered through determined innovation and an unrelenting desire to win; the performance of the RZR XP Turbo S is nothing short of intoxicating – giving you the confidence to push harder, further, faster than ever thought imaginable.

INTRODUCING THE NEW RZR XP® 1000 LINE-UP

RZR XP® 1000 DYNAMIX

Grab a DYNAMIX™ Edition and discover the terrain dominating savagery of active suspension.



RZR XP® 1000

> RZR XP® 1000

Ideally balanced extreme performance – instant response of 110-horsepower and 64-inch stance stability.



POLARIS RZR RS1

> MOST AGILE RZR® EVER

110 HORSEPOWER | **83IN** OPTIMAL WHEELBASE | **21IN** USABLE TRAVEL



POLARIS RIDE COMMAND



RZR XP® 1000 RIDE COMMAND

> RZR XP® 1000 RIDE COMMAND

Upgrade with a Ride Command® Edition, including off-road worthy 7" touchscreen that puts total control at your fingertips plus premium styling & LED lighting

ALL-NEW

RZR XP® TURBO S
168 HP



ALL-NEW

RZR XP® 4 TURBO S
168 HP



SINGLE SEAT

RZR® RS1
110 HP



TRAIL 50 IN WIDE

RZR® 570
45 HP



RZR® 900
75 HP



XTREME PERFORMANCE 64 IN WIDE

RZR XP® 1000
110 HP



AVAILABLE 4 SEAT

RZR XP® 1000 DYNAMIX
110 HP



AVAILABLE 4 SEAT

RZR XP® TURBO
168 HP



AVAILABLE 4 SEAT

SPORT 60 IN WIDE

RZR® S 900
75 HP



RZR® S 1000
110 HP



AVAILABLE 4 SEAT

FOREVER OUTDOORS™

ALL-NEW
SPORTSMAN XP® 1000



› FIND YOUR FREEDOM

With each breath, chilled mountain air presses against your chest as the first hints of sunlight expose a heavy blanket of morning dew. The outdoors is your passion. From the freedom of an open trail, the anticipation of the hunt, or the confidence to follow your instincts, this is the world of Sportsman®.



ALL-NEW
SPORTSMAN XP® 1000
PREMIUM

› BUILT TO WORK

90HP | **1,500LB** | **12IN**
TOWING CAPACITY | GROUND CLEARANCE



ALL-NEW
SPORTSMAN XP® 1000
HUNTER EDITION

› ENGINEERED FOR PASSION

- › NEW! KOLPIN® STRONGHOLD GUN SCABBARD
- › NEW! HAND AND THUMB WARMERS
- › NEW! FRONT AND REAR RACK EXTENDERS



ALL-NEW
SPORTSMAN® 850



ALL-NEW
SPORTSMAN® 850

FORGE NEW PATHS WITH LEGENDARY PERFORMANCE



SPORTSMAN® 570

ENGINEERED TO ENDURE

Far away from the concrete and steel of the city you'll find a place where the air is crisp, horizons beg to be chased and traditions are honored. For more than 30-years Sportsman® has brought you here with all-day comfort, unmatched storage and convenience, and hard-nosed performance that never quits.

RIDE HARDER

Up to 12" of Ground Clearance

GO FURTHER

Industry-Leading 8-Gallons of Sealed Storage

DO MORE

Up to 1,500 lbs of Towing Capacity

SPORTSMAN® 570



A SPORTSMAN® FOR EVERYONE

SPORTSMAN XP® 1000 PREMIUM

- » 90 HP
- » 12" GROUND CLEARANCE
- » FACTORY-INSTALLED ACCESSORIES



SPORTSMAN XP® 1000 HUNTER EDITION

- » 90 HP
- » 575 LB PAYLOAD CAPACITY
- » 11.5" GROUND CLEARANCE



SPORTSMAN® 850

- » 78 HP
- » 1,500 LB TOWING CAPACITY
- » 11.5" GROUND CLEARANCE



SPORTSMAN® 850 SP

- » 78 HP
- » 1,500 LB TOWING CAPACITY
- » CAST ALUMINUM WHEELS



SPORTSMAN® 570 SP



SPORTSMAN® 450

- » 33 HP
- » 10.5" GROUND CLEARANCE
- » 48" WIDE



SPORTSMAN® 570 SP

- » 44 HP
- » 1,500 LB TOWING CAPACITY
- » 11.5" GROUND CLEARANCE



SEE FULL SPECS ON PAGE 23

RIGHT SIZED RIDES



SINGLE SEAT FREEDOM



POLARIS RZR
FIT FOR FUN
RZR 170

POLARIS SPORTSMAN
CALIBRATED POWER
SPORTSMAN 110 EFI

POLARIS RANGER
UNRIVALED SAFETY
RANGER 150 EFI

EXPERIENCE THE TRAIL LESS TRAVELED
Take charge of the off-road with the control and confidence of Polaris ACE. The nimble handling and unrestrained adventure of an ATV are combined with the secured comfort and intuitive controls of a side-by-side for a riding experience like no other.

POLARIS ACE 900 XC

YOUTH VEHICLES

OUTLAW 50
AGES 6+



OUTLAW 110 EFI
AGES 10+



SPORTSMAN 110 EFI
AGES 10+



POLARIS ACE 150 EFI
AGES 10+



RANGER 150 EFI
AGES 10+



RZR 170
AGES 10+



PHOENIX 200
AGES 14+



CHOOSE YOUR POLARIS ACE®

- POLARIS ACE® 500**
- » 32 HP
 - » 8.2" SUSPENSION
 - » 1,500 LB TOWING CAP.
 - » 10" GROUND CLEARANCE
 - » 61.5" WHEELBASE



- POLARIS ACE® 570 EPS**
- » 44 HP
 - » 9" DUAL A-ARM SUSPENSION
 - » 1,500 LB TOWING CAP.
 - » 10.25" GROUND CLEARANCE
 - » EPS STANDARD
 - » 61.5" WHEELBASE



- POLARIS ACE® 900 XC**
- » 78 HP
 - » 12.3" SUSPENSION
 - » 13" GROUND CLEARANCE
 - » EPS STANDARD
 - » 67.5" WHEELBASE



		2-SEAT			3-SEAT			CREW			
		RANGER® EV AVAIL. EV-LI-ION	RANGER® 500	RANGER® 570 EPS AVAIL. BASE	RANGER® 570 FULL-SIZE	RANGER XP® 900 EPS, EPS PAINTED AVAIL. BASE	RANGER XP® 1000 EPS AVAIL. BASE	RANGER CREW® 570-4 EPS AVAIL. BASE	RANGER CREW® 570 FULL-SIZE	RANGER CREW® XP 900 EPS AVAIL. BASE	RANGER CREW® XP 1000 EPS AVAIL. BASE
ENGINE / DRIVE TRAIN	Engine Type	Single 48-Volt, High-Efficiency, AC-Induction Motor	4-Stroke Single-Cylinder	4-Stroke Single-Cylinder DOHC	4-Stroke Single-Cylinder DOHC	4-Stroke Twin-Cylinder DOHC	4-Stroke Twin-Cylinder DOHC	4-Stroke Single-Cylinder DOHC	4-Stroke Single-Cylinder DOHC	4-Stroke Twin-Cylinder DOHC	4-Stroke Twin-Cylinder DOHC
	Horsepower	30 HP	32 HP	44 HP	44 HP	68 HP	82 HP	44 HP	44 HP	68 HP	82 HP
	Drive System	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	High-Performance On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	High Performance On-Demand True AWD / 2WD / VersaTrac Turf Mode
	Engine Braking System	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Standard	Not Equipped	Not Equipped	Not Equipped	Standard
SUSPENSION	Front Suspension	MacPherson Strut 9" (22.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel	Dual A-Arm 10" (25.4 cm) Travel	Dual A-Arm 11" (27.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel	Dual A-Arm 10" (25.4 cm) Travel	Dual A-Arm 11" (27.9 cm) Travel
	Rear Suspension	Dual A-Arm, IRS 9" (22.9 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 11" (27.9 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 11" (27.9 cm) Travel
TIRES AND WHEELS	Front Tires	25 x 9-12; Carlisle	25 x 8-12; 489	25 x 8-12; 489	25 x 8-12; 489	26 x 9-12; PXT 25 x 10-12; 489	27 x 9-12; Maxxis® MU51 26 x 9-12; PXT	25 x 10-12; 489	25 x 10-12; 489	26 x 9-12; PXT	27 x 9-12; Maxxis® MU11 26 x 9-12; PXT
	Rear Tires	25 x 9-12; Carlisle	25 x 10-12; 489	25 x 10-12; 489	25 x 10-12; 489	26 x 11-12; PXT 25 x 11-12; 489	27 x 11-12; Maxxis® MU521 26 x 11-12; PXT	25 x 10-12; 489	25 x 10-12; 489	26 x 11-12; PXT	27 x 11-12; Maxxis® MU21 26 x 11-12; PXT
	Wheels	Stamped Steel	Stamped Steel	Aluminum Black Xcelerator Stamped Steel	Stamped Steel	Aluminum Black Xcelerator Stamped Steel	Aluminum Black Xcelerator 2.0 Stamped Steel	Aluminum Black Xcelerator Stamped Steel	Stamped Steel	Aluminum Black Xcelerator Stamped Steel	Aluminum Black Xcelerator 2.0 Stamped Steel
DIMENSIONS / CAPACITIES	Wheelbase	72" (182.9 cm)	73" (185.4 cm)	73" (185.4 cm)	79" (202 cm)	81" (206 cm)	81" (206 cm)	105" (266.7 cm)	107" (272.6 cm)	113" (287 cm)	113" (287 cm)
	Dry Weight	1,762 lb (799.2 kg)	1,065.9 lb (483 kg)	1,101.9 lb (501 kg) 1,073 lb (488 kg)	1,070.6 lb (486 kg)	1,342 lb (610 kg) 1,324.4 lb (601 kg)	1,565 lb (709.9 kg) 1,546 lb (701.3 kg)	1,351.2 lb (614 kg) 1,326.2 lb (603 kg)	1,392.5 lb (632 kg)	1,629 lb (738.9 kg) 1,612 lb (733 kg)	1,829 lbs (830kg) 1,810 lbs (821 kg)
	Overall Vehicle Size (L x W x H)	110 x 58 x 73" (279 x 147 x 185 cm)	110 x 58 x 73" (279 x 147 x 185 cm)	110 x 58 x 73" (279 x 147 x 185 cm)	114 x 60 x 74" (290 x 152 x 188 cm)	116.5 x 60 x 76" (296 x 152 x 193 cm)	142 x 60 x 73" (305 x 158 x 196 cm)	148.5 x 61 x 76" (377 x 155 x 193 cm)	148.5 x 61 x 76" (377 x 155 x 193 cm)	152 x 62.5 x 77" (386 x 158 x 196 cm)	152 x 62.5 x 77" (386 x 158 x 196 cm)
	Ground Clearance	10" (25.4 cm)	10" (25.4 cm)	10" (25.4 cm)	10.5" (26.7 cm)	12" (30.5 cm) 11.5" (29.2 cm)	13" (33 cm) 12.5" (31.8 cm)	10" (25.4 cm)	10.5" (26.7 cm)	11.3" (28.7 cm)	13" (33 cm) 12.5" (31.8 cm)
	Seating Capacity	2	2	2	3	3	3	4	6	6	6
	Fuel Capacity	N.A.	9 gal (34.1 L)	9 gal (34.1 L)	9 gal (34.1 L)	10 gal (37.9 L)	11.5 gal (43.5 L)	9 gal (34.1 L)	9 gal (34.1 L)	10 gal (37.9 L)	11.5 gal (43.5 L)
	Bed Box Dimensions (L x W x H)	32 x 42 x 11.5" (81 x 107 x 29 cm)	32 x 42 x 11.5" (81 x 107 x 29 cm)	32 x 42 x 11.5" (81 x 107 x 29 cm)	36.5 x 54 x 11.5" (93 x 137 x 29 cm)	36.5 x 54 x 11.5" (93 x 137 x 29 cm)	36.75 x 54.2 x 12.5" (93.3 x 137.8 x 31.8 cm)	32 x 42 x 11.5" (81 x 107 x 29 cm)	36.5 x 54 x 11.5" (93 x 137 x 29 cm)	36.5 x 54 x 11.5" (93 x 137 x 29 cm)	36.75 x 54.2 x 12.5" (93.3 x 137.8 x 31.8 cm)
	Box Capacity	500 lb (226.8 kg)	500 lb (226.8 kg)	500 lb (226.8 kg)	800 lb (363 kg)	1,000 lb (453.6 kg)	1,000 lb (453.6 kg)	500 lb (226.8 kg)	800 lb (363 kg)	1,000 lb (453.6 kg)	1,000 lb (453.6 kg)
	Payload Capacity	1,000 lb (453.6 kg)	1,000 lb (453.6 kg)	1,000 lb (453.6 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,250 lb (567 kg)	1,500 lb (680.4 kg)	1,750 lb (793.8 kg)	1,750 lb (793.8 kg)
Hitch Towing Rating	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	2,000 lb (907.2 kg)	2,500 lb (1,133.9 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	2,000 lb (907.2 kg)	2,500 lb (1,133.9 kg)	
FEATURES	Electronic Power Steering	Not Equipped	Not Equipped	Standard / Accessory Option	Not Equipped	Standard / Accessory Option	Standard	Standard / Accessory Option	Not Equipped	Standard / Accessory Option	Standard
	Adjustable Driver's Seat	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Standard Not Equipped	Standard Not Equipped	Not Equipped	Not Equipped	Standard on Silver Pearl Not Equipped	Standard Not Equipped
	Tilt Steering	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Color	Avalanche Grey, Polaris Pursuit® Camo Polaris Pursuit® Camo	Sage Green, Solar Red	Nara Bronze Sage Green, Polaris® Pursuit® Camo	Sage Green, Solar Red	Solar Red, Sage Green, Military Tan, Orange Madness, Silver Pearl Sage Green, Polaris® Pursuit® Camo	Steel Blue, Magnetic Gray, Pearl White, Polaris® Pursuit® Camo Sage Green	Nara Bronze Sage Green, Polaris® Pursuit® Camo	Sage Green	Polaris® Pursuit® Camo, Silver Pearl Sage Green	Sunset Red, Polaris® Pursuit® Camo, Pearl White Sage Green	

SPECIAL EDITIONS

NORTHSTAR EDITION
RANGER XP® 1000 FEATURES PLUS:

- » Premium RANGER Pro Shield™ Cab
- » Fixed-Glass Windshield with Wiper
- » Rear Glass Panel
- » Dome Light, Rear View Mirror
- » Heat, AC, Defrost



NORTHSTAR CREW EDITION
RANGER CREW® XP 1000 FEATURES PLUS:

- » Premium RANGER Pro Shield™ Cab
- » Fixed-Glass Windshield with Wiper
- » Rear Glass Panel
- » Dome Light, Rear View Mirror
- » Heat, AC, Defrost



HIGH LIFTER EDITION
RANGER XP® 1000 FEATURES PLUS:

- » Mud-Specific Gearing
- » High-Mount Air Intake and Vent Lines
- » 13.5" Ground Clearance
- » 28" Outlaw 2 Tires
- » Polaris® Pro 4,500 LB HD Winch



HIGH LIFTER CREW EDITION
RANGER CREW® XP 1000 FEATURES PLUS:

- » Mud-Specific Gearing
- » High-Mount Air Intake and Vent Lines
- » 13.5" Ground Clearance
- » 28" Outlaw 2 Tires
- » Polaris® Pro 4,500 LB HD Winch



TRAIL

SPORT

XTREME

MULTI

SPECIAL EDITIONS

	RZR® 570 AVAILABLE EPS	RZR® 900 AVAILABLE EPS	RZR® S 900 AVAILABLE EPS	RZR® S 1000 EPS	RZR® RS1	RZR XP® 1000 EPS	RZR XP® TURBO EPS	RZR XP® TURBO EPS DYNAMIX EDITION	RZR® XP TURBO S	RZR® S4 1000 EPS	RZR XP® 4 1000 EPS	RZR XP® 4 1000 EPS RIDE COMMAND	RZR XP® 4 TURBO EPS	RZR XP® 4 TURBO EPS DYNAMIX EDITION	RZR XP® 4 TURBO S
ENGINE / DRIVE TRAIN	ProStar® 570; 4-Stroke DOHC Single-Cylinder	ProStar® 900; 4-Stroke DOHC Twin-Cylinder	ProStar® 900; 4-Stroke DOHC Twin-Cylinder	ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	ProStar® 1000 H.O. 4-Stroke DOHC Twin Cylinder	ProStar® 1000 H.O.; 4-Stroke DOHC Twin-Cylinder	ProStar® Turbo H.O.; 4-Stroke DOHC Twin-Cylinder Turbocharged	ProStar Turbo H.O.; 4-Stroke DOHC Twin Cylinder Turbocharged	ProStar Turbo H.O.; 4-Stroke DOHC Twin Cylinder Turbocharged	ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	ProStar® 1000 H.O.; 4-Stroke DOHC Twin-Cylinder	ProStar 1000 H.O.; 4-Stroke DOHC Twin Cylinder	ProStar® Turbo H.O.; 4-Stroke DOHC Twin Cylinder Turbocharged	ProStar Turbo H.O.; 4-Stroke DOHC Twin Cylinder Turbocharged	ProStar Turbo H.O.; 4-Stroke DOHC Twin Cylinder Turbocharged
Horsepower	45 HP	75 HP	75 HP	100 HP	110 HP	110 HP	168 HP	168 HP	168 HP	100 HP	110 HP	110 HP	168 HP	168 HP	168 HP
Drive System	True On-Demand AWD / 2WD <i>High-Performance True On-Demand AWD / 2WD / VersaTrac Turf Mode</i>	True On-Demand AWD / 2WD <i>High-Performance True On-Demand AWD / 2WD</i>	True On-Demand AWD / 2WD <i>High-Performance True On-Demand AWD / 2WD</i>	High-Performance True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	High Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD	High-Performance True On-Demand AWD / 2WDm	High-Performance True On-Demand AWD / 2WD	High Performance True On-Demand AWD/2WD	High Performance True On-Demand AWD/2WD	High Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD
Engine Braking System	Not Equipped <i>Standard</i>	Standard	Standard	Standard	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped
SUSPENSION	Front Suspension Dual A-Arm with Stabilizer Bar and 9" (22.9 cm) Wheel Travel	Dual A-Arm with Stabilizer Bar and 10" (25.4 cm) Wheel Travel	Dual A-Arm with Stabilizer Bar and 12.25" (31.1 cm) Wheel Travel	Dual A-Arm with Stabilizer Bar and 12.25" (31.1 cm) Wheel Travel	Dual A-Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Dual A-Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Dual A-Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Dual A-Arm with Stabilizer Bar and 21" Travel	Dual A-Arm with Stabilizer Bar and 25" (63.5 cm) Travel	Dual A-Arm with Stabilizer Bar 12.25" (31.1 cm) Travel	Dual A-Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Dual A-Arm with 21" (53.4 cm) Travel	Dual A-Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Dual A-Arm with Stabilizer Bar and 21" Travel	Dual A-Arm with Stabilizer Bar and 25" (63.5 cm) Travel
Front Shocks	ZF Sachs®	ZF Sachs®	FOX® 2.0 PERFORMANCE PODIUM <i>2" Walker Evans® Needle</i>	2" Walker Evans® Needle	2" Walker Evans® Needle with 16-Position Adjustable Clickers	2" Walker Evans® Needle with 16-Position Adjustable Clickers	2" Walker Evans® Needle with 16-Position Adjustable Clickers	2.5 in FOX Podium Shocks with Live Valve (Electronically Controlled Damping)	FOX 2.5 Podium Internal Bypass Shocks with Live Valve (Electronically Controlled Damping)	FOX® 2.0 PODIUM X	2" Walker Evans® Needle with 16-Position Adjustable Clickers	2" Walker Evans® Needle with 16-Position Adjustable Clickers	2" Walker Evans® Needle with 16-Position Adjustable Clickers	2.5 in FOX Podium Shocks with Live Valve (Electronically Controlled Damping)	FOX 2.5 Podium Internal Bypass Shocks with Live Valve (Electronically Controlled Damping)
Rear Suspension	Dual A-Arm with Stabilizer Bar and 9.5" (24 cm) Wheel Travel	Dual A-Arm with Stabilizer Bar and 10" (25.4 cm) Wheel Travel	Dual A-Arm with Stabilizer Bar and 13.2" (33.5 cm) Wheel Travel	Dual A-Arm with Stabilizer Bar and 13.2" (33.5 cm) Wheel Travel	Trailing Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Trailing Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Trailing Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Trailing Arm with Stabilizer Bar and 21" Travel	Trailing Arm with Stabilizer Bar and 25" (63.5 cm) Travel	Dual A-Arm with Stabilizer Bar 13.2" (33.5 cm) Travel	Trailing Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Trailing Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Trailing Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Trailing Arm with Stabilizer Bar and 21" Travel	Trailing Arm with Stabilizer Bar and 25" (63.5 cm) Travel
Rear Shocks	ZF Sachs®	ZF Sachs®	FOX® 2.0 PERFORMANCE PODIUM <i>2" Walker Evans® Needle</i>	2" Walker Evans® Needle	2" Walker Evans® Needle with 16-Position Adjustable Clickers	2.5" Walker Evans® Needle with 16-Position Adjustable Clickers	2.5" Walker Evans® Needle with 16-Position Adjustable Clickers	2.5 in FOX Podium Shocks with Live Valve (Electronically Controlled Damping)	FOX 3.0 Podium Internal Bypass Shocks with Live Valve (Electronically Controlled Damping)	FOX® 2.0 PODIUM X	2.5" Walker Evans® Needle with 16-Position Adjustable Clickers	2.5" Walker Evans® Needle with 16-Position Adjustable Clickers	2.5" Walker Evans® Needle with 16-Position Adjustable Clickers	2.5 in FOX Podium Shocks with Live Valve (Electronically Controlled Damping)	FOX 3.0 Podium Internal Bypass Shocks with Live Valve (Electronically Controlled Damping)
TIRES AND WHEELS	Front Tires 25 x 8-12; Ancla® 25 x 8-12; Maxxis®	26 x 8-12; PXT	27 x 9-12; GBC® Dirt Commander	27 x 9-12; GBC® Dirt Commander	29 x 9-14 Maxxis Bighorn	29 x 9-14; Maxxis® Bighorn	29 x 9-14 Maxxis® Bighorn	29 x 9-14 Maxxis Bighorn	32 x 10-15; ITP COYOTE (8-Ply Rated)	27 x 9-12; GBC® Dirt Commander	29 x 9-14; Maxxis® Bighorn	29 x 9-14; Maxxis® Bighorn	29 x 9-14 Maxxis® Bighorn	29 x 9-14 Maxxis® Bighorn	32 x 10-15; ITP COYOTE (8-Ply Rated)
Rear Tires	25 x 10-12; Ancla® 25 x 10-12; Maxxis®	26 x 9-12; PXT	27 x 11-12; GBC® Dirt Commander	27 x 11-12; GBC® Dirt Commander	29 x 11-14 Maxxis Bighorn	29 x 11-14; Maxxis® Bighorn	29 x 11-14 Maxxis® Bighorn	29 x 11-14 Maxxis Bighorn	32 x 10-15; ITP COYOTE (8-Ply Rated)	27 x 11-12; GBC® Dirt Commander	29 x 11-14; Maxxis® Bighorn	29 x 11-14; Maxxis® Bighorn	29 x 11-14 Maxxis® Bighorn	29 x 11-14 Maxxis® Bighorn	32 x 10-15; ITP COYOTE (8-Ply Rated)
Wheels	Stamped Steel <i>Cast Aluminum</i>	Stamped Steel <i>Cast Aluminum</i>	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	15" Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	15" Cast Aluminum
DIMENSIONS / CAPACITIES	Wheelbase 77" (196 cm)	79" (200.7 cm)	79" (200.7 cm)	79" (200.7 cm)	83" (210.8 cm)	90" (228.6 cm)	90" (228.6 cm)	90" (228.6 cm)	90" (228.6 cm)	106.5" (270.5 cm)	117" (297.2 cm)	117" (297.2 cm)	117" (297.2 cm)	117" (297.2 cm)	117" (297.2 cm)
Dry Weight	996 lb (452 kg) <i>1,077 lb (489 kg)</i>	1,150 lb (522 kg) <i>1,176 lb (533 kg)</i>	1,204 lb (546 kg) <i>1,230 lb (558 kg)</i>	1,255 lb (560 kg)	1340 lbs (607.8kg)	1,369 lb (621 kg)	1,487 lbs (676 kg)	1,524 lbs (693 kg)	1,718 lbs (779.3 kg)	1,476 lb (670 kg)	1,659 lbs (754 kg)	1,586 lbs (719 kg)	1,698 lbs (772kg)	1,713 lbs (779 kg)	2,005 lbs (909 kg)
Overall Vehicle Size (L x W x H)	107.5 x 50 x 69" (273 x 127 x 175.2 cm)	108 x 50 x 69.5" (274.3 x 127 x 176.5 cm)	106 x 60 x 71.5" (269.2 x 152.4 x 181.6 cm)	108 x 60 x 71.5" (274.3 x 152.4 x 181.6 cm)	112" x 64" x 73.7" (284.5 x 162.6 x 187.3 cm)	119 x 64 x 73.7" (302.2 x 162.6 x 187.3 cm)	119 x 64 x 73.7" (302.2 x 162.6 x 187.3 cm)	119 x 64 x 73.75" (302.2 x 162.6 x 187.3 cm)	122" x 74.5" x 8" (309.9 x 189.2 x 190.5 cm)	138.1 x 60 x 71.7" (350.8 x 152.4 x 182.1 cm)	146 x 64 x 73.7" (370.8 x 162.6 x 187.3 cm)	146 x 64 x 73.8" (370.8 x 162.6 x 187.3 cm)	146 x 64 x 73.8" (370.8 x 162.6 x 187.3 cm)	146 x 64 x 73.75" (370.8 x 162.6 x 187.3 cm)	149" x 73.75" x 76.5" (378.5 x 187.3 x 194.3 cm)
Ground Clearance	10.5" (26.7 cm)	11" (27.9 cm)	12.5" (31.8 cm)	12.5" (31.8 cm)	13" (33 cm)	13.5" (34.3 cm)	13.5" (34.3 cm)	13.5" (34.3 cm)	16" (40.6 cm)	12.5" (31.8 cm)	13.5" (34.3 cm)	13.5" (34.3 cm)	13.5" (34.3 cm)	13.5" (34.3 cm)	16" (40.6 cm)
Fuel Capacity	7.25 gal (27.4 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)
Bed Box Dimensions (L x W x H)	20 x 40 x 9" (51 x 102 x 23 cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20 cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20 cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20cm)	20.5" x 23" x 4.1" (52 x 58 x 10.4 x 3 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)
Rear Rack Capacity	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	50 lb (22.7 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)
Payload Capacity	740 lb (335.6 kg)	740 lb (335.6 kg)	740 lb (335.6 kg)	740 lb (335.6 kg)	300 lb (136.1kg)	740 lb (335.6 kg)	740 lb (335.6 kg)	740 lb (335.6 kg)	740 lb (335.6 kg)	900 lb (408.2 kg)	300 lb (136.1 kg)	900 lb (408.2 kg)	900 lb (408.2 kg)	900 lb (408.2 kg)	900 lb (408.2 kg)
Lighting	Halogen, 50W <i>Halogen, 55W low / 60W high</i>	Halogen, 55W Low / 60W High & Red LED Tail / Brake Lights	Halogen, 55W Low / 60W High & Red LED Tail / Brake Lights	Halogen, 55W Low / 60W High & Red LED Tail / Brake Lights	White LED, Low/High & Red LED Tail / Brake Lights	White LED, Low/High & Red LED Tail / Brake Lights	White LED, Low / High & Red LED Tail / Brake Lights	Front Blacked Out White LED Low/High w/ Accent Lights & Red LED Tail / Brake / Accent Lights	White LED, Low/High & Red LED Tail / Brake Lights	Halogen, 55W Low / 60W High & Red LED Tail / Brake Lights	White LED, Low / High & Red LED Tail / Brake Lights	White LED, Low / High & Red LED Tail / Brake Lights	White LED, Low / High & Red LED Tail / Brake Lights	White LED, Low / High & Red LED Tail / Brake Lights	Front Blacked Out White LED Low/High w/ Accent Lights & Red LED Tail / Brake / Accent Lights



RZR XP® 1000 DYNAMIX
SAME FEATURES AS RZR XP® 1000 PLUS:

- » Dynamix® Active Suspension
- » Dynamix® Visualizer
- » Ride Command® 7" Glove-Touch Display
- » Rear-Facing Camera
- » 900 Watt Stator
- » Available in a 4-Seat



RZR XP® 1000 RIDE COMMAND
SAME FEATURES AS RZR XP® 1000 PLUS:

- » 7" Glove-Touch Display
- » AM/FM Antenna
- » In-door Audio
- » Front and Rear Wired Cameras


[DOWNLOAD THE FREE RIDE COMMAND® APP](#)



RZR XP® 4 1000 RIDE COMMAND
SAME FEATURES AS RZR XP® 4 1000 PLUS:


- » 7" Glove-Touch Display
- » AM/FM Antenna
- » In-door Audio
- » Front and Rear Wired Cameras

[DOWNLOAD THE FREE RIDE COMMAND® APP](#)




















RZR XP® 1000 HIGH LIFTER
SAME FEATURES AS RZR XP® 1000 PLUS:

- » Front Bull Bumper with Winch Hook
- » Polaris® 4,500 lb Integrated Winch
- » High-Clearance Lower Control Arms
- » High-Clearance Lower Radius Rods
- » Outlaw® 2 Tires
- » High-Mount Rear Intake System
- » Rearview Mirror and Half Doors
- » Available in a 4-Seat



RZR XP® 1000 TRAILS & ROCKS
SAME FEATURES AS RZR XP® 1000 PLUS:

- » Front Bull Bumper with Tow Loop
- » Polaris® 4,500 lb Integrated Winch
- » High-Clearance Lower Control Arms
- » High-Clearance Lower Radius Rods
- » ProArmor® Crawler XG Tires with Beadlock Wheel
- » Rock Sliders and HMW Skid Plate
- » Rearview Mirror
- » High-Visibility Front Fender
- » Flares and Click-6 Harnesses

		REC / UTILITY						SPORT / UTILITY				2-UP / UTILITY					MUD & SPORT		
																			
ENGINE / DRIVE TRAIN	Engine Type	ProStar® 500cc, 4-Stroke SOHC Single-Cylinder	ProStar® 500cc, 4-Stroke SOHC Single-Cylinder	ProStar® 567cc, 4-Stroke DOHC Single-Cylinder	ProStar® 567cc, 4-Stroke DOHC Single-Cylinder	ProStar® 567cc, 4-Stroke DOHC Single-Cylinder	ProStar® 567cc, 4-Stroke DOHC Single-Cylinder	ProStar® SOHC 4-Stroke Twin Cylinder	ProStar® SOHC 4-Stroke Twin Cylinder	ProStar® 952cc, 4-Stroke SOHC Twin-Cylinder	ProStar® 952cc, 4-Stroke SOHC Twin-Cylinder	ProStar® 567cc, 4-Stroke DOHC Single-Cylinder	ProStar® 567cc, 4-Stroke DOHC Single-Cylinder	ProStar® 567cc, 4-Stroke DOHC Single-Cylinder	ProStar® 4-Stroke SOHC Twin Cylinder	ProStar® 4-Stroke SOHC Twin Cylinder	ProStar® 952cc, 4-Stroke SOHC Twin-Cylinder	ProStar® SOHC 4-Stroke Twin Cylinder	
	Horsepower	33 HP	33 HP	44 HP	44 HP	44 HP	44 HP	78 HP	78 HP	90 HP	90 HP	44 HP	44 HP	44 HP	78 HP	88 HP	85 HP	78 HP	
	Drive System	True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	High Performance True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	High Performance True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	High-Performance True On-Demand AWD / 2WD	True On-Demand AWD / 2WD
	Engine Braking System / Active Descent Control	Not Equipped / Not Equipped	Not Equipped / Not Equipped	Not Equipped / Not Equipped	Standard / Not Equipped	Standard / Standard	Standard / Standard	Standard / Not Equipped	Standard / Standard	Standard / Standard	Standard / Standard	Standard / Standard	Not Equipped / Not Equipped	Not Equipped / Not Equipped	Standard / Standard	Standard / Standard	Standard / Standard	Standard / Standard	Not Equipped / Not Equipped
SUSPENSION	Front Suspension	MacPherson Strut, 8.2" (20.8 cm) Travel	MacPherson Strut, 8.2" (20.8 cm) Travel	MacPherson Strut, 8.2" (20.8 cm) Travel	MacPherson Strut, 8.2" (20.8 cm) Travel	Dual A-Arm, 8.2" (20.8 cm) Travel	Dual A-Arm, 8.2" (20.8 cm) Travel	High Clearance Arched Dual A-Arm 9" (22.9 cm) Travel	High Clearance Arched Dual A-Arm 9" (22.9 cm) Travel	High-Clearance Arched Dual A-Arm, 9" (22.9 cm) Travel	High Clearance Arched Dual A-Arm 9" (22.9 cm) Travel	MacPherson Strut, 8.2" (20.8 cm) Travel	MacPherson Strut, 8.2" (20.8 cm) Travel	Dual A-Arm, 8.2" (20.8 cm) Travel	Dual A-Arm, 9" (22.9 cm) Travel	Dual A-Arm, 9" (22.9 cm) Travel	High Clearance Arched Dual A-Arm 7.4" (18.8 cm) Travel	High Clearance Arched Dual A-Arm 7.4" (18.8 cm) Travel	
	Rear Suspension	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	High Clearance Arched Dual A-Arm, Rolled IRS, 10.25" (26 cm) Travel	High Clearance Arched Dual A-Arm, Rolled IRS, 10.25" (26 cm) Travel	High-Clearance Arched Dual A-Arm, Rolled IRS, 10.25" (26 cm) Travel	High Clearance Arched Dual A-Arm, Rolled IRS, 10.25" (26 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, IRS 9.5" (24.1 cm) Travel	Dual A-Arm, Rolled IRS, 10.25" (26 cm) Travel	Dual A-Arm, Rolled IRS, 10.25" (26 cm) Travel	High Clearance Arched Dual A-Arm, Rolled IRS, 6.7" (17 cm) Travel	High Clearance Arched Dual A-Arm, Rolled IRS, 6.7" (17 cm) Travel	
TIRES & WHEELS	Front Tires	24 x 8-12; NS388	24 x 8-12; NS388	25 x 8-12; 489	25 x 8-12; 489	26 x 8-14; CST / PXT 6-Ply Radial	26 x 9; PXT	26 x 8; 489	26 x 8; CST	SP/XP 26 x 8; CST XP Premium 27 x 9; Duro Power Grip V2	26 x 9; PXT	25 x 8-12; 489	25 x 8-12; 489	26 x 8-14; CST	26 x 8; CST	26 x 9; PXT	29.5 x 9.5; Outlaw 2	29.5 x 9.5; Outlaw 2	
	Rear Tires	24 x 10-12; NS388	24 x 10-12; NS388	25 x 10-12; 489	25 x 10-12; 489	26 x 8-14; CST / PXT 6-Ply Radial	26 x 11; PXT	26 x 10; 489	26 x 10; CST	SP/XP 26 x 10; CST XP Premium 27 x 11; Duro Power Grip V2	26 x 11; PXT	25 x 10-12; 489	25 x 10-12; 489	26 x 10-14; CST	26 x 10; CST	26 x 11; PXT	29.5 x 9.5; Outlaw 2	29.5 x 9.5; Outlaw 2	
	Wheels	Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel	Cast Aluminum	Cast Aluminum	Stamped Steel	Aluminum	Cast Aluminum	Cast Aluminum	Stamped Steel	Stamped Steel	Cast Aluminum	Cast Aluminum	Cast Aluminum	Aluminum	Steel	
DIMENSIONS / CAPACITIES	Wheelbase	50.5" (128.3 cm)	50.5" (128.3 cm)	50.5" (128.3 cm)	50.5" (128.3 cm)	50.5" (128.3 cm)	50.5" (128.3 cm)	53 in (134.6 cm)	53" (134.6 cm)	53" (134.6 cm)	53" (134.6 cm)	56" (142.2 cm)	56" (142.2 cm)	56" (142.2 cm)	57" (144.8 cm)	57" (144.8 cm)	53" (134.6 cm)	53" (134.6 cm)	
	Dry Weight	701 lb (318 kg) 713 lb (323 kg)	721 lb (328 kg)	704 lb (330 kg) 716 lb (325 kg)	755 lb (343 kg)	730 lb (332 kg)	753 lb (342 kg)	771 lb (351 kg)	785 lb (359 kg)	805 lb (366 kg)	805 lb (366 kg)	788 lb (358 kg)	728 lb (330 kg) 739 lb (336 kg)	773 lb (351 kg)	804 lb (365 kg)	886 lb (403 kg)	974 lb (441 kg)	921 lb (417 kg)	
	Overall Vehicle Size (L x W x H)	83 x 48 x 47" (210.8 x 121.9 x 119.4 cm)	84 x 48 x 47" (213 x 121.9 x 119.4 cm)	83 x 48 x 48" (210.8 x 121.9 x 121.9 cm)	83 x 48 x 48" (210.8 x 121.9 x 121.9 cm)	83 x 48 x 48" (210.8 x 121.9 x 121.9 cm)	83 x 48 x 48" (210.8 x 121.9 x 121.9 cm)	83.25 x 47.6 x 50.75" (211.4 x 120.9 x 128.9 cm)	83.25 x 47.6 x 50.75" (211.4 x 120.9 x 128.9 cm)	83.25 x 47.6 x 50.75" (211.4 x 120.9 x 128.9 cm)	83.25 x 47.6 x 50.75" (211.4 x 120.9 x 128.9 cm)	89 x 48 x 48" (226.1 x 121.9 x 121.9 cm)	86 x 48 x 48" (218.4 x 121.9 x 121.9 cm)	86 x 48 x 48" (218.4 x 121.9 x 121.9 cm)	86.5 x 47.6 x 58.25" (219.7 x 120.9 x 147.9 cm)	86.5 x 47.6 x 58.25" (219.7 x 120.9 x 147.9 cm)	83.25 x 47.6 x 50.75" (211.4 x 120.9 x 128.9 cm)	83 x 49 x 52" (210 x 124 x 132 cm)	
	Ground Clearance	10.5" (26.6 cm)	10.5" (26.6 cm)	11" (27.9 cm)	11" (27.9 cm)	11.5" (29.2 cm)	11.5" (29.2 cm)	11.5" (29.2 cm)	11.5" (29.2 cm)	11.5" (29.2 cm)	11.5" (29.2 cm)	11" (27.9 cm)	11" (27.9 cm)	11.5" (29.2 cm)	11.2" (28.5 cm)	11.2" (28.5 cm)	13.5" (34.3 cm)	13.5" (34.3 cm)	
	Seat Height	33.25" (84.5 cm)	33.25" (84.5 cm)	33.75" (85.7 cm)	33.7" (85.7 cm)	34.2" (87 cm)	34.3" (87 cm)	37" (94 cm)	37" (94 cm)	37" (94 cm)	37" (94 cm)	33.7" (85.7 cm)	33.7" (85.7 cm)	34.2" (87 cm)	35.7" (90.8 cm)	35.7" (90.8 cm)	39" (99 cm)	39" (99 cm)	
	Fuel Capacity	4.5 gal (17.0 L)	4.5 gal (17.0 L)	4.5 gal (17.0 L)	4.5 gal (17.0 L)	4.5 gal (17.0 L)	4.5 gal (17.0 L)	5.2 gal (19.9 L)	5.2 gal (19.9 L)	5.2 gal (19.9 L)	5.2 gal (19.9 L)	6.7 gal (26.3 L)	6.75 gal (26.3 L)	6.7 gal (26.3 L)	5.2 gal (19.9 L)	5.2 gal (19.9 L)	5.2 gal (19.9 L)	5.2 gal (19.9 L)	
	Rear Box Dimensions (L x W x H)	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.	37.5 x 19.5 x 6.5" (95 x 49.5 x 16.5 cm)	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.	
	Front/Rear Rack Capacity	90 lb (40.8 kg) / 180 lb (81.6 kg)	90 lb (40.8 kg) / 180 lb (81.6 kg)	90 lb (40.8 kg) / 180 lb (81.6 kg)	90 lb (40.8 kg) / 180 lb (81.6 kg)	90 lb (40.8 kg) / 180 lb (81.6 kg)	90 lb (40.8 kg) / 180 lb (81.6 kg)	120 lb (55 kg) / 240 lb (110 kg)	120 lb (55 kg) / 240 lb (110 kg)	120 lb (55 kg) / 240 lb (110 kg)	120 lb (55 kg) / 240 lb (110 kg)	90 lb (40.8 kg) / 400 lb (180 kg)	90 lb (40.8 kg) / 180 lb (81.6 kg)	90 lb (40.8 kg) / 180 lb (81.6 kg)	120 lb (55 kg) / 240 lb (110 kg)	120 lb (55 kg) / 240 lb (110 kg)	N.A. / 75 lb (34 kg)	N.A. / 75 lb (34 kg)	
	Payload Capacity	485 lb (220 kg)	485 lb (220 kg)	485 lb (220 kg)	485 lb (220 kg)	485 lb (220 kg)	485 lb (220 kg)	575 lb (261 kg)	575 lb (261 kg)	575 lb (261 kg)	575 lb (261 kg)	705 lb (320 kg)	575 lb (261 kg)	485 lb (220 kg)	575 lb (261 kg)	575 lb (261 kg)	290 lb (132 kg)	290 lb (132 kg)	
Hitch Towing Rating	1,225 lb (555.7 kg)	1,225 lb (555.7 kg)	1,225 lb (555.7 kg)	1,225 lb (555.7 kg)	1,500 lb (680 kg)	1,500 lb (680 kg)	1,500 lb (680.4 kg)	1,500 lbs (748.4 kg)	1,500 lbs (680.4 kg)	1,500 lb (680.4 kg)	1,225 lb (555.7 kg)	1,225 lb (555.7 kg)	1,500 lb (680 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)		
Colors	Sage Green, Indy Red, Orange Burst	Ghost Gray	Sage Green, Velocity Blue, Polaris® Pursuit® Camo, Sage Green, Velocity Blue, Polaris® Pursuit® Camo	Ghost Gray	Crimson Metallic, Magnetic Gray Metallic	Polaris® Pursuit® Camo	Sage Green, Titanium Metallic	White Lightning, Magnetic Gray Metallic, Polaris® Pursuit® Camo	Radar Blue, Steel Blue	Polaris® Pursuit® Camo	Sage Green	Indy Red, Velocity Blue	Silver Pearl	Silver Pearl	Crimson Metallic	Stealth Black	Cruiser Black		

	2-SEAT			4-SEAT		SPECIAL EDITIONS		
	POLARIS® GENERAL® 1000	POLARIS® GENERAL® 1000 PREMIUM	POLARIS® GENERAL® 1000 DELUXE	POLARIS® GENERAL® 4 1000	POLARIS® GENERAL® 4 1000 RIDE COMMAND	POLARIS® GENERAL® 1000 RIDE COMMAND	POLARIS® GENERAL® 1000 HUNTER EDITION	POLARIS® GENERAL® 1000 LIMITED EDITION
ENGINE/DRIVE TRAIN	Engine Type: ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	Engine Type: ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	Engine Type: ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	Engine Type: ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	Engine Type: ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	Engine Type: ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	Engine Type: ProStar® 1000; 4-Stroke DOHC Twin-Cylinder	Engine Type: ProStar® 1000; 4-Stroke DOHC Twin-Cylinder
Horsepower	100 HP	100 HP	100 HP	100 HP	100 HP	100 HP	100 HP	100 HP
Drive System	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode	On-Demand True AWD / 2WD / VersaTrac Turf Mode
Engine Braking System	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
SUSPENSION	Front Suspension: Dual A-Arm with Stabilizer Bar and 12.2" (31.1 cm) Travel	Front Suspension: Dual A-Arm with Stabilizer Bar and 12.2" (31.1 cm) Travel	Front Suspension: Dual A-Arm with Stabilizer Bar and 12.2" (31.1 cm) Travel	Front Suspension: Dual A-Arm with Stabilizer Bar and 12.2" (31.1 cm) Travel	Front Suspension: Dual A-Arm with Stabilizer Bar and 12.2" (31.1 cm) Travel	Front Suspension: Dual A-Arm with Stabilizer Bar and 12.2" (31.1 cm) Travel	Front Suspension: Dual A-Arm with Stabilizer Bar and 12.2" (31.1 cm) Travel	Front Suspension: Dual A-Arm with Stabilizer Bar and 12.2" (31.1 cm) Travel
Front Shocks	ZF Sachs® Twin Tube	ZF Sachs® Twin Tube	FOX® 2.0 PODIUM X QS3	FOX® 2.0 PODIUM X QS3	FOX® 2.0 PODIUM X QS3	FOX® 2.0 PODIUM X QS3	ZF Sachs® Twin Tube	ZF Sachs® Twin Tube
Rear Suspension	Dual Arm IRS with Stabilizer Bar and 13.2" (33.5 cm) Travel	Dual Arm IRS with Stabilizer Bar and 13.2" (33.5 cm) Travel	Dual Arm IRS with Stabilizer Bar and 13.2" (33.5 cm) Travel	Dual Arm IRS with Stabilizer Bar and 13.2" (33.5 cm) Travel	Dual Arm IRS with Stabilizer Bar and 13.2" (33.5 cm) Travel	Dual Arm IRS with Stabilizer Bar and 13.2" (33.5 cm) Travel	Dual Arm IRS with Stabilizer Bar and 13.2" (33.5 cm) Travel	Dual Arm IRS with Stabilizer Bar and 13.2" (33.5 cm) Travel
Rear Shocks	ZF Sachs® Twin Tube	ZF Sachs® Twin Tube	FOX® 2.0 PODIUM X QS3	FOX® 2.0 PODIUM X QS3	FOX® 2.0 PODIUM X QS3	FOX® 2.0 PODIUM X QS3	ZF Sachs® Twin Tube	ZF Sachs® Twin Tube
TIRES & WHEELS	Front Tires: 27 x 9-12 NHS; CST Clincher	Front Tires: 27 x 9-14; Maxxis® Coronado	Front Tires: 27 x 9-14; Maxxis® Coronado	Front Tires: 27 x 9-14; Dirt Commander	Front Tires: 27 x 9-14; Dirt Commander	Front Tires: 27 x 9-14; Maxxis® Coronado	Front Tires: 27 x 9-14; Maxxis® Coronado	Front Tires: 27 x 9-14; Maxxis® Coronado
Rear Tires	27 x 11-12 NHS; CST Clincher	27 x 11-14; Maxxis® Coronado	27 x 11-14; Maxxis® Coronado	27 x 11-14; Dirt Commander	27 x 11-14; Dirt Commander	27 x 11-14; Maxxis® Coronado	27 x 11-14; Maxxis® Coronado	27 x 11-14; Maxxis® Coronado
Wheels	Stamped Steel	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum
DIMENSIONS / CAPACITIES	Wheelbase: 81" (206 cm)	Wheelbase: 81" (206 cm)	Wheelbase: 81" (206 cm)	Wheelbase: 113" (287 cm)	Wheelbase: 113" (287 cm)	Wheelbase: 81" (206 cm)	Wheelbase: 81" (206 cm)	Wheelbase: 81" (206 cm)
Dry Weight	1,430 lb (648 kg)	1,491 lb (676 kg)	1,544 lb (700 kg)	1,857 lb (842 kg)	1,860 lb (842 kg)	1,544 lb (700 kg)	1,491 lb (676 kg)	1,491 lb (676 kg)
Overall Vehicle Size (L x W x H)	116.4 x 62.5 x 73.8" (295.6 x 158.7 x 187 cm)	116.4 x 62.5 x 73.8" (295.6 x 158.7 x 187 cm)	118.2 x 62.5 x 75" (300 x 158.7 x 190.5 cm)	150.2 x 62.5 x 75" (381.5 x 158.7 x 190.5 cm)	150.2 x 62.5 x 75" (381.5 x 158.7 x 190.5 cm)	118.2 x 62.5 x 75" (300 x 158.7 x 190.5 cm)	118.2 x 62.5 x 73.8" (300 x 158.7 x 187 cm)	118.2 x 62.5 x 73.8" (300 x 158.7 x 187 cm)
Ground Clearance	12" (30.5 cm)	12" (30.5 cm)	12" (30.5 cm)	12" (30.5 cm)	12" (30.5 cm)	12" (30.5 cm)	12" (30.5 cm)	12" (30.5 cm)
Fuel Capacity	9.5 gal (35.9 L)	9.5 gal (35.9 L)	9.5 gal (35.9 L)	9.5 gal (35.9 L)	9.5 gal (35.9 L)	9.5 gal (35.9 L)	9.5 gal (35.9 L)	9.5 gal (35.9 L)
Bed Box Dimensions (L x W x H)	27.5 x 43.1 x 11.6" (69.8 x 109 x 29.5 cm)	27.5 x 43.1 x 11.6" (69.8 x 109 x 29.5 cm)	27.5 x 43.1 x 11.6" (69.8 x 109 x 29.5 cm)	27.5 x 43.1 x 11.6" (69.8 x 109 x 29.5 cm)	27.5 x 43.1 x 11.6" (69.8 x 109 x 29.5 cm)	27.5 x 43.1 x 11.6" (69.8 x 109 x 29.5 cm)	27.5 x 43.1 x 11.6" (69.8 x 109 x 29.5 cm)	27.5 x 43.1 x 11.6" (69.8 x 109 x 29.5 cm)
Rear Rack Capacity	600 lb (272 kg)	600 lb (272 kg)	600 lb (272 kg)	600 lb (272 kg)	600 lb (272 kg)	600 lb (272 kg)	600 lb (272 kg)	600 lb (272 kg)
Payload Capacity	1,100 lb (499 kg)	1,100 lb (499 kg)	1,100 lb (499 kg)	1,280 lb (580 kg)	1,280 lb (580 kg)	1,100 lb (499 kg)	1,100 lb (499 kg)	1,100 lb (499 kg)
Electronic Power Steering	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Other Features		Polaris® HD 4,500 lb Winch Sport Low Profile Front Bumper	Polaris® HD 4,500 lb Winch, Sport Low Profile Front Bumper, ProFit Sport Roof, Premium 8-Speaker Bluetooth® AM/FM Soundbar, Convex Rear View Mirror	Polaris® HD 4,500 lb Winch Sport Low Profile Front Bumper	Polaris® HD 4,500 lb Winch, Sport Low Profile Front Bumper, ProFit Sport Roof, Premium 8-Speaker Bluetooth® AM/FM Soundbar, Convex Rear View Mirror, Front & Rear On-board Cameras	Polaris® HD 4,500 lb Winch, Sport Low Profile Front Bumper, ProFit Sport Roof, Premium 8-Speaker Bluetooth® AM/FM Soundbar, Convex Rear View Mirror, Front & Rear On-board Cameras	Polaris® HD 4,500 lb Winch, Sport Low Profile Front Bumper, Lock & Ride® Dual Gun Scabbard, Polaris® Gun Boots (Qty 2)	Polaris® HD 4,500 lb Winch Sport Low Profile Front Bumper, Lock & Ride® Tip Down Headache Rack
Colors	White Lighting	Havasu Red	Orange Rust, Titanium Metallic	Matte White Metallic	Black Pearl	Black Pearl	Polaris® Pursuit® Camo	Cruiser Black Breakout Camo

	OUTLAW® 50	OUTLAW® 110 EFI	SPORTSMAN® 110 EFI	POLARIS ACE® 150 EFI	RZR® 170 EFI	PHOENIX® 200	RANGER® 150 EFI
ENGINE	Age: 6+	Age: 10+	Age: 10+	Age: 10+	Age: 10+	Age: 14+	Age: 14+
Engine Type	49cc, 4-Stroke Single-Cylinder	112cc, 4-Stroke Single-Cylinder	112cc, 4-Stroke Single-Cylinder	149cc, 4-Stroke Single-Cylinder	169cc, 4-Stroke Single-Cylinder	196cc, 4-Stroke Single-Cylinder	196cc, 4-Stroke Single-Cylinder
Fuel System	Carbureted	EFI	EFI	EFI	EFI	Carbureted	Carbureted
Cooling	Air	Air	Air	Air/Oil	Fan	Air	Air
DRIVE TRAIN / SUSPENSION	Transmission/Final Drive: Automatic PVT Forward; O-Ring Chain	Transmission/Final Drive: Automatic PVT F/N/R; O-Ring Chain	Transmission/Final Drive: Automatic PVT F/N/R; O-Ring Chain	Transmission/Final Drive: Automatic PVT F/N/R; O-Ring Chain	Transmission/Final Drive: Automatic PVT F/N/R; O-Ring Chain	Transmission/Final Drive: Automatic PVT F/N/R; Shaft	Transmission/Final Drive: Automatic PVT F/N/R; Shaft
Drive System	2WD	2WD	2WD	2WD	2WD	2WD	2WD
Front Suspension	Single A-Arm with 3" (7.6 cm) Travel	Single A-Arm with 5" (12.7 cm) Travel	Single A-Arm with 5" (12.7 cm) Travel	Dual A-Arm 5.1" (13 cm) Travel	Single A-Arm with 5" (12.7 cm) Travel	Dual A-Arm with 7" (17.8 cm) Travel	Dual A-Arm with 7" (17.8 cm) Travel
Rear Suspension	Mono-Shock Swingarm with 3" (7.6 cm) Travel	Mono-Shock Swingarm with 6" (15.2 cm) Travel	Mono-Shock Swingarm with 6" (15.2 cm) Travel	Swingarm Dual Shocks with 6" (15.2 cm) Travel	Swingarm Dual Shocks with 5" (12.7 cm) Travel	Mono-Shock Swingarm with 6.5" (16.5 cm) Travel	Mono-Shock Swingarm with 6.5" (16.5 cm) Travel
TIRES & WHEELS	Front Tires: 16 x 6.5-7	Front Tires: 19 x 7-8	Front Tires: 19 x 7-8	Front Tires: 22 x 7-10	Front Tires: 19 x 7-8	Front Tires: 21 x 7-10	Front Tires: 21 x 7-10
Rear Tires	16 x 8-7	18 x 9.5-8	18 x 9.5-8	22 x 10-10	20 x 10-9	20 x 10-9	20 x 10-9
Wheels	Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel	Stamped Steel
DIMENSIONS / CAPACITIES	Wheelbase: 33" (83.8 cm)	Wheelbase: 41.5" (105.4 cm)	Wheelbase: 41.5" (105.4 cm)	Wheelbase: 65" (165.1 cm)	Wheelbase: 65" (165.1 cm)	Wheelbase: 45" (114.3 cm)	Wheelbase: 45" (114.3 cm)
Dry Weight	215 lb (98 kg)	278 lb (126 kg)	289 lb (131 kg)	572 lb (260 kg)	532 lb (241 kg)	420 lb (191 kg)	420 lb (191 kg)
Overall Vehicle Size (L x W x H)	48 x 31.5 x 28" (121.9 x 80 x 71.1 cm)	61.3 x 36.8 x 38.5" (155.6 x 93.3 x 97.8 cm)	61.8 x 36.8 x 38.5" (156.8 x 93.3 x 97.8 cm)	85 x 48 x 58" (215.9 x 121.9 x 147.3 cm)	85 x 48 x 55" (215.9 x 121.9 x 139.7 cm)	65 x 42 x 42" (165.1 x 106.7 x 106.7 cm)	65 x 42 x 42" (165.1 x 106.7 x 106.7 cm)
Ground Clearance	4" (10.2 cm)	4" (10.2 cm)	4" (10.2 cm)	9" (22.9 cm)	6" (15.2 cm)	5.7" (14.5 cm)	5.7" (14.5 cm)
Seat Height	23" (58.4 cm)	27" (68.6 cm)	27" (68.6 cm)	N.A.	N.A.	32" (81.3 cm)	32" (81.3 cm)
Fuel Capacity	1.2 gal (4.5 L)	1.6 gal (5.9 L)	2.0 gal (7.8 L)	2.5 gal (9.5 L)	2.5 gal (9.5 L)	2.5 gal (9.5 L)	2.5 gal (9.5 L)
Rear Box Dimensions (L x W x H)	N.A.	N.A.	N.A.	17 x 32 x 3" (43.2 x 81.3 x 7.6 cm)	N.A.	N.A.	N.A.
Front/Rear Rack or Box Capacity	N.A.	N.A.	15 lb / 30 lb (6.8 kg / 13.6 kg)	50 lb (22.7 kg)	N.A.	N.A.	N.A.
Payload Capacity	N.A.	N.A.	45 lb (20.4 kg)	50 lb (22.7 kg)	N.A.	N.A.	N.A.
Colors	Pink Power, Lime Squeeze	Pink Power, Lime Squeeze	Velocity Blue	Indy Red	Cruiser Black / Lime Squeeze or Bright White / Indy Red	Avalanche Gray	Indy Red

POLARIS®

OFF-ROAD VEHICLES

POLARIS.COM/OFFROAD

POLARIS
GENERAL

POLARIS
RANGER

POLARIS
RZR

POLARIS
SPORTSMAN

POLARIS
ACE

WARNING: The Polaris off-road vehicles can be hazardous to operate and is not intended for on-road use. Driver must be at least 16 years old with a valid driver's license to operate. Passengers must be at least 12 years old. Drivers and passengers should always wear helmets, eye protection, and seat belts. Always use cab nets or doors (as equipped). Never engage in stunt driving, and avoid excessive speeds and sharp turns. Riding and alcohol/drugs don't mix. All drivers should take a safety training course. Call 800-342-3764 for additional information. Check local laws before riding on trails. All claims based on IHS Automotive, Polk total full-size new U.S. Automatic ATV registrations between October 2015 and December 2016. HIGH LIFTER and HIGH LIFTER OUTLAW are trademarks of HIGH LIFTER PRODUCTS, INC. Bluetooth® is a registered trademark of Bluetooth Sig. Inc. All rights reserved. ©2017 Polaris Industries Inc. all pricing, specifications, claims and information contained in this brochure are based on information available at the time of publication and are subject to change without notice.

Youth models have special age restrictions: the Polaris RZR® 170 and ACE 150 are intended for operators age 10 and older, 50-cc ATV models are intended for operators ages 6 and over, 110-cc ATV models are intended for operators ages 10 and older, and the 200-cc ATV is intended for operators age 14 and older. All Polaris youth vehicles require adult supervision at all times for operators under age 16.

PN: 9930530